

Film-Tech

The information contained in this Adobe Acrobat pdf file is provided at your own risk and good judgment.

These manuals are designed to facilitate the exchange of information related to cinema projection and film handling, with no warranties nor obligations from the authors, for qualified field service engineers.

If you are not a qualified technician, please make no adjustments to anything you may read about in these Adobe manual downloads.

www.film-tech.com

Smart/EZ Polarity Checker User's Manual

Description:

The Smart/EZ Polarity Checker allows to verify signal polarity at each step of the signal transmission path in recording studios, theatres, sound reinforcement systems etc. with easy-handling and flexibility being the most important features of the test devices.

The test system consists of two separate units:

1. the signal generator
2. the indicator

Both units may use and process either electrical or acoustical signals thus being able to check microphones, split-transformers, loudspeaker systems, cables and recording equipment.

The output of the generator may be adjusted by means of a detented pot whereas the input sensitivity of the indicator is selected by a mic-line switch.

On both units the user may select pin 2 or pin 3 of the XLR connector to exhibit positive polarity thus being enabled to check sound systems using different wiring standards without the need to reinterpret the indicator's display and so avoiding a possible error source.

The default selector position defines pin 2 to be of positive polarity. The generator's output (XLR-male) is floating balanced and may be used in unbalanced systems without problems as long as a bridge between pin 2 and pin 3 is avoided, e.g. when testing loudspeaker systems using the generator's loudspeaker direct drive capability.

The indicator may be used in a balanced or unbalanced mode.

Function:

The signal generator generates a sequence of unidirectional pulses which are radiated through the internal loudspeaker or may be picked up at the generator's XLR output connector.

After having passed the device-under-test the signal is fed either into the indicator's electrical input equipped with an XLR female connector or picked up acoustically using the indicator's internal condenser microphone.

The indicator processes the input signal and assesses the slope of the pulse being either positive or negative. The result of this process is displayed on the coloured display of the indicator.

Instructions for use:

1. Loudspeaker polarity

The signal generator may be directly connected to the loudspeaker under test, since it's electrical output is capable of driving even low impedances with sufficient level. Should the generator's output level suffice, e.g. due to high ambient noise level, it may be connected to an amplifier with known properties to drive the loudspeaker. Signal level should then be adjusted to deliver a clean, distortion-free acoustic output. The indicator's mode selector switch has to be in it's MIC-INT position while the indicator's internal microphone has to be placed in the nearfield of the loudspeaker. In case of testing horn loudspeakers, the microphone should NOT be inside the horn, which holds especially true for bass horns.

The result of the test process may now be read from the LED-Display:

GREEN LED flashing - 'In Phase'

RED LED flashing - 'Out of Phase'

2. Microphone polarity

The indicator's mode selector has to be in its MIC-EXT position and the microphone connected to the input XLR-connector. The generator's acoustic test signal is now picked up with the microphone-under-test placed in close proximity to the generator's internal loudspeaker. The sensitivity of the indicator in its MIC-EXT usually is sufficient to test even unresponsive microphones using the test signal of the generator. In case of disadvantageous conditions, e.g. extremely unresponsive microphones or high ambient noise, an amplifier with known properties should be looped into the signal path either at the generator's output powering a known loudspeaker or at the input of the indicator thus amplifying the microphone signal.

In case the microphone-under-test is phantom-powered an appropriate power supply has to be provided.

3. Polarity of line-level devices

With the mode selector of the indicator in its LINE-IN position split transformers, amplifiers, X-Overs and other signal processing devices may be checked.

The test signal is picked up from the generator's XLR output and fed into the device-under-test. The output level of the signal generator is variable using the detented pot on top of the unit thus avoiding input overload.

The output signal of the device-under-test is directly fed into the XLR input connector of the indicator.

To check amplifier polarity the amplifier should not be set to excessive gain as input voltages beyond 50V may damage the indicator. The best procedure is to increase amplifier gain until a stable display is achieved. NOTE that ALL cables used in your test configuration must be checked for polarity changes as well!!!

4. Polarity of signal recording devices

Checking the polarity of recording equipment requires only slight changes in the test procedure. While the wiring scheme and the polarity checker settings do not change, the generator's output signal is now recorded and may be checked for polarity changes when played back.

5. Variable pulse repetition rate

As an option, the pulse generator may be ordered with variable pulse repetition rate. This option is useful when aligning delay times in delayed decentralized sound systems. Pulse generators with this option exhibit an additional trimpot which can be adjusted using an appropriate screwdriver.

6. Error sources

In case of a definitely wrong display at first the correct position of the 'PIN 2 - PIN 3' selector should be verified. Connect the generator's output directly to the indicator's input and set both switches correspondingly. The indicator should then flash the GREEN LED.

In case there is no LED flashing at all, either the signal level is too low, the mode selector is in an inappropriate position or pin 2 and pin 3 are shorted due to incorrect wiring.

Specifications:

Generator:

- o electrical and acoustical output
 - o output XLR male
 - o switches
 - o level control line
 - o power supply
 - o battery life
 - o dimensions
 - o weight
- 0.0 ... 1.5V (8 Ohm)
ON/OFF, PIN2/PIN3
detented pot
1 x 9V PP3
50 hours using alkaline cells
60 x 110 x 35 (45) mm
310 g (incl. battery)

Indicator

- o electrical and acoustical input
 - o input XLR female
 - o switches
 - o display
 - o power supply
 - o battery life
 - o dimensions
 - o weight
- MIC-EXT: 10 ... 500mV/ 1 kOhm
LINE-IN: 0.5 ... 50V/ 10 kOHM
ON/OFF; BAL./UNBAL.;
PIN2/PIN3; MIC-INT/MIC-EXT/
LINE-IN
LED red/green
1 x 9V PP3
50 hours using alkaline cells
60 x 110 x 35 (40) mm
280 g (incl. battery)

- o handcrafted by 'veteran audio craftsmen'